

Economy Friction Wrists

Economy Wrist	Part Number	Dimensions	Feature
	52159 Al 64g	Diameter: 2 in.	• Variable friction using compressible discs
	52162 SS 134g	Diameter: 2 in.	
	59491 Ti 93g	Diameter: 2 in.	
	58690 Al 68g LR	Diameter: 2 in.	
OW Oval Wrist, Economy	Part Number	Dimensions	Feature
	51622 Al 72g	Length: 2 ¼ in. Width: 1 ½ in.	• Oval wrist with variable friction using compressible discs
	58700 Al 76g LR	Length: 2 ¼ in. Width: 1 ½ in.	
Economy Wrist with Straps	Part Number	Dimensions	Feature
	52163 SS 170g	Diameter: 2 in.	• Anchor straps allow for heavy duty use
	59463 Ti 140g	Diameter: 2 in.	

WA Disarticulation Friction Wrist	Part Number	Dimensions	Feature
	52119 SS 57g	Diameter: 1 ¾ in.	• Wrist disarticulation model
	52117 SS 71g LR	Diameter: 1 ¾ in.	

Constant friction Wrists

WedgeGrip Wrist	Part Number	Dimensions	Feature
	62351 Al 62g	Diameter: 1 ¾ in.	• Constant friction using metal on metal contact for longer wear
	61897 Al 79g	Diameter: 2 in.	
WedgeGrip Wrist Oval	Part Number	Dimensions	
	62354 Al 79g	Length: 2 in. Width: 1 ½ in.	
	61970 Al 93g	Length: 2 ¼ in. Width: 1 ½ in.	

CAPP Wrist	Part Number	Dimensions	Feature
	55108 D 16g	Diameter: 1 ½ in.	• Lightweight and shapeable wrist for passive and lightweight devices
	55109 D 22g	Diameter: 1 ¾ in.	
	55110 D 30g	Diameter: 2 in.	
Shapeable Passive Hand Wrist	Part Number	Dimensions	
	62022 ABS 21g	Length: 1.9 in. Width: 1.4 in.	
	62021 ABS 28g	Length: 2.2 in. Width: 1.5 in.	
	62020 ABS 36g	Length: 2.6 in. Width: 1.7 in.	

WE Infant Friction Wrist	Part Number	Dimensions	Feature
	52142 Al 28g NR	Diameter: 1 ¼ in.	• Constant friction wrist using nylon thread compression with set screw • Uses replaceable friction unit except infant size (52142)
WE Friction Wrist	Part Number	Dimensions	
	52147 Al 42g	Diameter: 1 ½ in.	
	52156 Al 57g	Diameter: 1 ¾ in.	
	58688 Al 65g LR	Diameter: 1 ¾ in.	
	52160 Al 74g	Diameter: 2 in.	
	58684 Al 78g LR	Diameter: 2 in.	
OW Oval Friction Wrist	Part Number	Dimensions	
	51618 Al 57g	Length: 2 in. Width: 1 ½ in.	
	51623 Al 71g	Length: 2 ¼ in. Width: 1 ½ in.	
	58697 Al 75g LR	Length: 2 ¼ in. Width: 1 ½ in.	
OW Friction Wrist Insert	Part Number	Dimensions	
	52151 Al 30g	½-20 Insert	

Flexion

APRL Child Flexion Wrist	Part Number	Dimensions	Feature
	52176 Al 42g	Diameter: 1 ¼ in. Height: 1 ¼ in.	• Constant friction • Resistance at 0 and 36 degrees of flexion • Proximal ½-20 thread

FW Flexion Friction Wrist	Part Number	Dimensions	Feature
	51078 Al 49g	Diameter: 1 ½ in.	• Constant friction • Can lock in 0, 30, or 50 degrees or flexion • For use with hooks only
	51084 Al 71g	Diameter: 1 ¾ in.	
	51100 Al 92g	Diameter: 2 in.	
	51101 SS 221g	Diameter: 2 in.	

Sierra Flexion Wrist	Part Number	Dimensions	Feature
	52371 Al 113g	Diameter: 2 in. Height: 1 ¼ in.	• Constant friction • Can lock in 0, 25, or 50 degrees of flexion, friction rotation • Proximal ½-20 thread

SS Stainless Steel	ABS ABS
Al Aluminum	g Product Weight, includes Insert
Ti Titanium	LR Lamination Ring Model
D Delrin	NR Non-removable Insert

Quick Disconnect: Locking Wrist

Quick Disconnect Wrist	Part Number	Dimensions	Feature
	62342 Al 89g	Diameter: 1 ¾ in.	<ul style="list-style-type: none"> • Push button to unlock rotation (light push) and remove terminal device (harder push) • Insert included with each wrist
	61862 Al 105g	Diameter: 2 in.	
Quick Disconnect Oval Wrist	Part Number	Dimensions	
	62343 Al 92g	Length: 2 in. Width: 1 ½ in.	
	61922 Al 105g	Length: 2 ¼ in. Width: 1 ¾ in.	
Quick Disconnect Insert	Part Number	Thread	
	61860 SS 23g	½-20 Insert	

FM Quick Change Wrist	Part Number	Dimensions	Feature
	51043 Al 92g	Diameter: 2 in.	<ul style="list-style-type: none"> • Push button to unlock rotation (light push) and remove terminal device (harder push) • Insert included with each wrist
	51044 SS 170g	Diameter: 2 in.	
	58297 Al 112g LR	Diameter: 2 in.	
	62436 Ti 166g LR	Diameter: 2 in.	
FM Quick Change Wrist Insert	Part Number	Thread	
	51052 SS 29g	½-20 Insert	

Quick Disconnect: Friction Wrist

Friction Disconnect Wrist	Part Number	Insert	Dimensions	Feature
	58151 Al 102g LR	SS Insert	Diameter: 1 ¾ in.	<ul style="list-style-type: none"> • Free and friction mode by push button • Lamination ring on all models • Insert included with each wrist
	58152 Al 129g LR	SS Insert	Diameter: 2 in.	
Friction Disconnect Oval Wrist	Part Number	Insert	Dimensions	
	58150 Al 122g LR	SS Insert	Length: 2 ¼ in. Width: 1 ¾ in.	
	Friction Disconnect Insert	Part Number	Thread	
	58153 SS 32g	½-20 Insert		

WD Quick Change Wrist	Part Number	Insert	Dimensions	Feature
	52127 Al 98g	Al Insert	Diameter: 2 in.	<ul style="list-style-type: none"> • Free, locked, and friction modes activated by alternating rotation of the wrist • Insert included with each wrist
	52128 Al 120g	SS Insert	Diameter: 2 in.	
	53896 SS 200g	SS Insert	Diameter: 2 in.	
WD Quick Change Wrist Insert	Part Number	Thread		
	50527 Al 18g	½-20 Insert		
	50528 SS 40g	½-20 Insert		

Specialty

Four Function Wrist	Part Number	Dimensions	Feature
	62268 Al 247g	Diameter: 2 in. Height: 2 in.	<ul style="list-style-type: none"> • Four Functions: Flexion: 0, 25, 50 degrees Extension Pronation: 180 degrees Supination: 180 degrees • 18 Rotational Locking Positions • Combination of the Sierra and Rotational Wrists

Rotational Wrist	Part Number	Dimensions	Feature
	61875 Al 104g	Diameter: 2 in.	<ul style="list-style-type: none"> • Cable pull achieves 360 degrees rotation with 18 locking positions

SS Stainless Steel	ABS ABS
Al Aluminum	g Product Weight, includes Insert
Ti Titanium	LR Lamination Ring Model
D Delrin	NR Non-removable Insert